PRODUCT NAME	CAS#
Boron Trichloride	10294-35-3
TRADE NAME AND SYNONYMS	DOT I.D. NO.
Boron Trichloride	UN 1741
CHEMICAL NAME AND SYNONYMS	DOT HAZARD CLASS
Boron Trichloride, Boron Chloride, Trichloroborane	Division 2.3 (Poison Gas)
ISSUE DATE AND REVISIONS	FORMULA
Revised March 2007	BCl ₃

HEALTH HAZARD DATA

EMERGENCY OVERVIEW

Boron Trichloride is a poisonous, corrosive, high pressure gas, which can cause eye, skin, and respiratory tract burns. Also, it may cause kidney damage.

SYMPTOMS OF EXPOSURE

<u>Inhalation</u>: May cause coughing, choking sensation, chest pain, pulmonary edema and death. Concentrations as low as 50 molar ppm may be fatal if inhaled for approximately one hour.

Skin Contact: May cause "stinging" of the skin, local redness and swelling. At high concentrations will cause severe burns.

Eye Contact: Very irritating with redness and swelling of the conjunctiva. High concentrations can cause burns of the cornea.

TOXICOLOGICAL PROPERTIES

 TLV-TWA
 5 ppm

 LC₅₀
 2541 ppm

RECOMMENDED FIRST AID TREATMENT

PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE TO BORON TRICHLORIDE. RESCUERS SHOULD BE EQUIPPED WITH ADEQUATE PERSONAL PROTECTIVE APPARATUS.

<u>Inhalation</u>: Remove patients to fresh air. Give artificial respiration if not breathing. Qualified personnel may give oxygen if breathing is difficult.

Skin Contact: Remove contaminated clothing and flush affected area with water.

<u>Eye Contact</u>: PERSONS WITH POTENTIAL EXPOSURE TO BORON TRICHLORIDE SHOULD NOT WEAR CONTACT LENSES. Immediately flush eyes with copious quantities of water and continue flushing for at least 15 minutes.

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES

Decomposes in hot water releasing hydrogen chloride.

PHYSICAL DATA

BOILING POINT	CRITICAL TEMPERATURE	
54.5 °F	353.8°F	
MOLECULAR WEIGHT	DENSITY, LIQUID (0 °C)	
117.17	1.373g/ml	
SOLUBILITY IN WATER	DENSITY, GAS (21.1 °C, 1 atm)	
Soluble in cold water; decomposes in hot water	4.85g/ml	
EVAPORATION RATE	SPECIFIC GRAVITY (AIR=1)	
N/A	4.04 at 70°F	
APPEARANCE AND ODOR		
Colorlage and with an imitating parid oder		

Colorless gas with an irritating acrid odor.

FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	AUTO IGNITION TEMPERATURE	FLAMMABLE LIMITS % BY VOLUME		
N/A	N/A	lel N/A	uel N/A	
EXTINGUISHING MEDIA Nonflammable gas. Use water to keep fire exposed cylinders cool. Shut-off cylinder when leaking. Wear full protective clothing including self-contained breathing apparatus.				

SPECIAL FIRE FIGHTING PROCEDURES

In case of fire, move cylinders out of affected area immediately.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Most combustible materials burn in Boron Trichloride as they do in oxygen. Reacts explosively or forms explosive compounds with many chemicals likes acetylene, turpenine, ether, ammonia gas, hydrogen, and finely divided metals. Under intense heat and/or flame, the cylinder can rupture.

REACTIVITY DATA

STABILITY		CONDITIONS TO AVOID		
Unstable		N/A		
Stable	Х			
INCOMPATIBILITY (Materials to avoid)			
Reacts with most substances including water (forms HCl and H ₃ BO ₃), organics, hydrogen, ammonia, grease, oxygen, alcohols, nitrogen peroxide.				
HAZARDOUS POLYM	ERIZATION	HAZARDOUS THERMAL DECOMPOSITION PRODUCTS		
May Occur		Thermal decomposition will produce toxic fumes of chlorides.		
Will Not Occ	ur X	BCl ₃ is hydrolyzed by water or moisture to form hydrochloric and		
		boric acids.		

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Evacuate all personnel from affected area. Wear Self-Contained Breathing Apparatus and protective clothing.

WASTE DISPOSAL METHOD

Waste disposal must be in accordance with appropriate Federal, State, and local regulations. For emergency disposal assistance, contact HSG for specific advice.

SPECIAL PROTECTION INFORMATION

RESPIRTORY PROTECTION (Specify type)		
Positive pressure air line with mask or self-conta	ained breathing apparatus should be available for	
emergency use.		
VENTILATION	SPECIAL	
Hood with forced ventilation.	N/A	
MECHANICAL (Gen.)	OTHER	
N/A	N/A	
LOCAL EXHAUST		
To prevent accumulation above the TWA.		
PROTECTIVE GLOVES		
Neoprene or nitrile.		
EYE PROTECTION		
Safety goggles or glasses		
OTHER PROTECTIVE EQUIPMENT		
Safety shoes and protective clothing.		

SPECIAL PRECAUTIONS*

SPECIAL LABELING INFORMATION		
DOT Shipping Name: Boron Trichloride	DOT Hazard Class: Division 2.3	
DOT Shipping Label: Poison Gas	I.D. No.:	UN 1741

SPECIAL HANDLING RECOMMENDATIONS

Use only in well-ventilated areas. Valve protection caps must remain in place unless cylinder is secured with valve outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure-reducing regulator when connecting cylinder to lower pressure piping or system. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.

SPECIAL STORAGE RECOMMENDATIONS

Protect cylinders from physical damage. Store in cool, dry, well-ventilated area away from heavy traffic areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 130°F. Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in – first out" inventory system to prevent full cylinders being stored for excessive periods of time.

OTHER RECOMMENDATIONS OR PRECAUTIONS

Keep equipment meticulously dry. Compressed gas cylinders should not refilled except by qualified producers of compressed gases.

Information contained in this material safety data sheet is offered without charge for use by technically qualified personnel at their discretion and risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed no warranty of any kind is made with respect thereto. This information is not intended as a license to operate under or a recommendation to practice or infringe any patent of this Company or others covering any process, composition of matter or use.

Since the Company shall have no control of the use of the product described herein, the Company assumes no liability for loss or damage incurred from the proper or improper use of such product.